Corrigendum

Corrigendum to "Data driven model for heat load prediction in buildings connected to District Heating by using smart heat meters" [Energy 239, Part D, 2022, 122318]

Mikel Lumbreras [a, *], Roberto Garay-Martinez [b], Beñat Arregi [b], Koldobika Martin-Escudero [a], Gonzalo Diarce [a], Margus Raud [c], Indrek Hagu [c]

[a] ENEDI Research Group, Department of Energy Engineering, Faculty of Engineering of Bilbao, University of the Basque Country UPV/EHU, Pza, Ingeniero Torres Quevedo 1, Bilbao, 48013, Spain
[b] TECNALIA, Basque Research and Technology Alliance (BRTA), Bizkaia Science and Technology Park, Astondo Bidea 700, Derio, Spain
[c] GREN Eesti, Turu 18, Tartu, Estonia

The authors regret to inform that, even after careful revisions in all stages of the manuscript, a relevant typographic error has been found in the published version of the paper. The error is found in the definition of the so-called Q-algorithm in Eq. (1), where the selection among two formulae is performed based on the actual heat load (Q) compared to a reference heat load (Q_{REF}). The correct formulation for equation can be found in Eq. (1) below.

$$Q_{alg} \; Q = \begin{cases} \alpha_1 \cdot T_{OUT} + \alpha_2 \cdot G_T + \alpha_3 \cdot W_S + \alpha_4 \cdot W_D, & Q > Q_{REF} \\ \alpha_0, & Q \leq Q_{REF} \end{cases} \qquad (1)$$

The authors would like to apologise for any inconvenience caused.